

# AVT EMC 4K MiniCam

High resolution (UHD) Camera  
especially for EMC- and test laboratories,  
as well as general applications



Fully compatible with Rohde & Schwarz AdvISE  
visual inspection software and MiniCam programs



- ⇒ **4K Camera** for EMC labs and test fields with high interference immunity
- ⇒ different resolutions selectable (640 x 360 up to 3840 x 2160)
- ⇒ **Pan/Tilt/Zoom inside camera** controlled by software
- ⇒ easy to use in hardware and software
- ⇒ high quality vision sensor
- ⇒ USB Video Class (UVC) compliant
- ⇒ data transmission with optical fibers (USB 3.0)
- ⇒ small housing in slim design
- ⇒ high field immunity > 100 V/m
- ⇒ options:
- ⇒ integrated rechargeable battery (5 Ah)
- ⇒ optic lens for different angles
- ⇒ higher interference immunity

**MADE IN GERMANY**

# Ordering informations

**AVT - EMC4K - xxx - X - X**

emc hardened  
4K MiniCam

focal length  
032: 3,2 mm  
045: 4,5 mm  
068: 6,8 mm  
120: 12,0 mm

version  
01: version 1

internal battery  
-: without battery  
A: with battery

**Example: AVT-EMC4K-120-01**

## Technical specifications

<b>Optics</b>	
focal length	3,2   4,5   6,8   12,0
focus distance	103°   68°   48°   30°
field of view	70°   42°   28°   17°
optical format, sensor	1/2,5", CMOS Sony IMX317
<b>Resolutions</b>	
small size (below HD)	640x360, 640x480, 800x600, 960x540
HD-resolutions	1280x720, 1280x 960, 1600x1200, 1920x1080
2K-resolutions	2048x1536, 2688x1512, 2592x1944
4K-resolution (UHD)	3840x2160 (Pixel Größe 1,62 µm x 1,62 µm)
frame rates	30 fps (alle Auflösungen)
<b>General informations</b>	
USB video class compliant	yes, Microsoft WHQL certified
temperature operating range	-10°C ... 50°C
length of fiber optic cable	10 m, 20 m, 30 m, 50 m, 70 m, 100 m
data- and control interface on PC/Laptop	USB 3.0 (plug A)
<b>Electrical specifications</b>	
supply voltage (DC, 5 V typ.)	<b>min</b> 4,85 V   <b>max</b> 5,25 V
power (camera without battery charging)	0,6 W   2,6 W
current (operation / charging battery / operation and charging)	0,11 / 0,0 / 0,11 A   0,52 / 2,0 / 2,52 A
delivery of power supply / charger / external battery	yes / sold as option / sold as option
<b>Dimensions</b>	
Length of the camera without connectors	126 mm
Width	50 mm
Height (with foot)	50 mm (60 mm)
Weight	370 g

## Contact

Errors and changes excepted.

AVT GmbH • Automatisierungs- und Verfahrenstechnik • Am Hammergrund 1 • 98693 Ilmenau • Germany  
Tel: +49 (0)3677 6479-56 • Fax: +49 (0)3677 6479-69 • Web: [www.avt-ilmenau.de](http://www.avt-ilmenau.de) • Mail: [info@avt-ilmenau.de](mailto:info@avt-ilmenau.de)